



3M™ Overhead Projector Model 9050

Dependability

Enhance your visuals and keep the room lights up for note taking with the dependable 3M Overhead Projector Model 9050. Focus your images once, and the rack and pinion mechanism keeps them focused between use. The rugged Model 9050 is designed to deliver reliable performance day after day. The wide-angle lens projects a large, clear image – even in small rooms. The fold-down arm makes storage easy and the built-in thermostat protects from overheating. The Model 9050 is made in the U.S.A.

KEY FEATURES

- 2,500 lumens of light enhance your visuals and let you keep the room lights on for note-taking
- Wide-angle lens delivers beautiful images even when projector is close to the wall
- Engineered for long lamp life, so you change lamps less frequently (Average 130 hours)
- Die-cast zinc arm assembly is tough, yet lightweight
- Built-in post gives you a convenient place to wrap cord before transporting
- Compact for easy transport; arm folds down for easy storage and more secure transport
- No more fumbling around; your controls are right at your fingertips
- Cool stage keeps transparency film from curling; quiet fan doesn't distract from your presentation
- Five-year warranty covers parts and labor
- Made in the U.S.A.

TECHNICAL SPECIFICATIONS

Optical Performance

- Head: Open, singlet (one element), wide angle; focal length: 293 mm (11.5")
- Illumination: 2500 lumens typical
- Design: Transmissive with folded optical system
- Stage aperture: 267 mm x 267 mm (10.5" x 10.5")
- Stage temperature: 45°C (115°F)

Lamp Description

- Lamp ejector: Yes
- Lamp changer: No (1 lamp included)
- Type: ENX
- Life: 130 hours, using the 3M 9050
- Voltage: 82 volts
- Watts: 360 watts

Physical Characteristics

- Width: 361 mm (14.2")
- Depth: 425 mm (16.75")
- Height (top of head): 711 mm (28")
- Weight: 7.8 kg (17.2 lbs)

Electrical Requirements

- Voltage rating: 120 VAC, 60 Hz
- Power cord length: 4.6 m (15')
- Agency approval: UL/CUL
- International models available with 100v/220v/240v FNT lamp and

A/4 stage.

Mechanical

- Lamp interrupt switch: Shuts off power to the lamp when top access cover is opened.
- Thermal protection circuit: Cuts power to the lamp if the projector exceeds safe operating temperature.

Order Number

78-9236-5693-4

Specifications subject to change.

1-800-328-1371

www.3M.com/meetings



3M Visual Systems Division
Building A145-5N-01
6801 River Place Blvd.
Austin, TX 78726-9000

3M Canada
P.O. Box 5757
London, Ontario, Canada
N6A 4T1

3M Mexico, S.A. de C.V.
Apartado Postal 14-139
Mexico, D.F. 07070
Mexico



*Recycled paper,
40% pre-consumer,
10% post-consumer*

Litho in U.S.A. © 3M 1998
78-6970-5602-2