



3M™ Overhead Projector Model 9200

Perfect Presentations

The 3M Overhead Projector Model 9200 puts high brightness in a stylish, sophisticated package that fits any office decor. Discreet, contemporary styling keeps eyes on you and your visuals. Its lightweight, compact design fits on most standard overhead carts. The Model 9200 has a triplet lens allowing images to be viewed in high resolution. The two-lamp system provides uninterrupted presentations. The 3M Overhead Projector Model 9200 is easy to use, rugged and folds down for easy transport and storage.

KEY FEATURES

- 3,500 lumens of light enhance your visuals and let you keep the room lights on for note-taking
- Once you focus your images, they stay focused
- Cool stage keeps transparency film from curling
- Quiet fan doesn't distract from your presentation
- No more fumbling around; your controls are right at your fingertips
- Die-cast zinc arm assembly is tough, yet lightweight
- Built-in posts give you a convenient place to wrap the cord before transporting
- Compact for easy transport; arm folds down for easy storage and more secure transport
- Triplet lens design gives you dynamic image clarity
- External color-tuning dial gets rid of blue or brown corners, giving you a brilliant white screen
- High-low lamp intensity switch adjusts for your needs: high for full-color transparencies, low for other visuals; low setting extends lamp life
- Two lamps mean you always have an extra on hand, and changing lamps is as easy as it is convenient
- Five-year warranty covers parts and labor
- Made in the U.S.A.

TECHNICAL SPECIFICATIONS

Optical Performance

- Head: Triplet (three element), high-resolution
- Focal length: 342 mm (13.5")
- Illumination: 3500 lumens typical
- Design: Transmissive with folded optical system
- Stage aperture: 267 mm x 267 mm (10.5" x 10.5")
- Stage temperature: 45°C (115°F)

Lamp Description

- Lamp ejector: Yes
- Lamp changer: Yes (2 lamps included)
- Type: FXL
- Voltage: 82 volts
- Watts: 410 watts

Physical Characteristics

- Width: 361 mm (14.2")
- Depth: 425 mm (16.75")
- Height (top of head): 711 mm (28")
- Weight: 8.86 kg (19.5 lbs)

Electrical Requirements

- Voltage rating: 120 VAC, 60 Hz
- Power cord length: 4.6 m (15')
- Agency approval: UL/CUL
- International models available with 100v/220v/240v/ FNT lamp and A/4 stage

Mechanical

- Lamp interrupt switch: Shuts off power to the lamp when top access cover is opened
- Thermal protection circuit: Cuts power to the lamp if the projector exceeds safe operating temperature

Order Number
78-9236-5654-6

Specifications subject to change without notice.

1-800-328-1371

www.3M.com/meetings



3M Visual Systems Division
Building A145-5N-01
6801 River Place Blvd.
Austin, TX 78726-9000

3M Canada
P.O. Box 5757
London, Ontario, Canada
N6A 4T1

3M Mexico, S.A. de C.V.
Apartado Postal 14-139
Mexico, D.F. 07070
Mexico



*Recycled paper,
40% pre-consumer,
10% post-consumer*

Litho in U.S.A. © 3M 1998
78-6970-5607-1